

Stop the Morphological Cycle, I Want to Get Off: Modeling the Development of Fusion

Micha Elsner, Martha Booker Johnson, Stephanie Antetomaso, Andrea D. Sims

Department of Linguistics

The Ohio State University

elsner.14, johnson.6713, antetomaso.2, sims.120@osu.edu

Abstract

Historical linguists observe that many fusional (unsegmentable) morphological structures developed from agglutinative (segmentable) predecessors. Such changes may result when learners fail to acquire a phonological alternation, and instead, “chunk” the altered versions of morphemes and memorize them as underlying representations. We present a Bayesian model of this process, which learns which morphosyntactic properties are chunked together, what their underlying representations are, and what phonological processes apply to them. In simulations using artificial data, we provide quantitative support to two claims about agglutinative and fusional structures: that variably-realized morphological markers discourage fusion from developing, but that stress-based vowel reduction encourages it.

1 Introduction

While modern typologists reject the wholesale categorization of languages as isolating, agglutinative or fusional (Haspelmath, 2009), they still recognize a distinction between morphological structures which can be easily segmented and those which cannot (Plank, 1999). In ones with morphological *fusion* (or *cumulation*), multiple morphosyntactic properties (MSPs)¹ are realized by a single morph with no immediately segmentable pieces.² For instance, Turkish *tarla-lar-ı* and Old English *feld-a* both indicate ‘field-PL.ACC’ (Plank, 1999), but the Old English suffix cannot be further analyzed whereas the Turkish word has separate number and case morphemes.

¹We use *morphosyntactic category* to refer to sets of properties; cross-linguistically common categories are TENSE, PERSON, NUMBER, etc., and morphosyntactic properties are PRESENT, PAST, etc.

²Following practice in morphology, we use the term *morph* to refer to (only) the form part of a morpheme.

Along with this taxonomic distinction comes a historical origin story, sometimes called the *morphological cycle* (Hock and Joseph, 1996)[183]. Through processes of phonological reduction, independent function words become attached to content words as agglutinative inflections. Further phonological reduction or sound changes blur the boundaries between morphemes, leading to fusion. Finally, affixes may become so non-transparent that their association with MSPs is lost (demorphologization) at which point new function words may be recruited to replace them, beginning the cycle anew.

Morphological change is more various and more complicated than this simple story suggests, and this cycle isn’t the only way in which fusion can arise (Grünthal, 2007; Igartua, 2015; Karim, 2019). However, it is one way that has been observed. In this paper we focus on the role of phonological processes in the transition between agglutination and fusion. Morphological reanalysis often results from an interaction between the phonology of a language and the learning mechanism. Specifically in this context, morphemes are most likely to fuse if the environments in which they occur, and the phonological processes triggered by those environments, are vulnerable to reanalysis, which is to say, to mis-learning. The question becomes: which kinds of phonological processes are likely to make morphological constructions vulnerable to reanalysis, and which are not?

In order to test the role that phonological processes play in making agglutinative structures vulnerable to reanalysis, we provide a formal learning model³ for morphological systems whose internal representations clearly distinguish between agglutination and fusion. The model extends Cot-

³Code and data at github.com/melsner/scil2019-fusion.

terell et al. (2015), learning a Bayesian model which maps from sets of MSPs to surface forms in three steps: selection of a morphological template, concatenation of underlying forms, and phonology. We validate the model by testing on a series of artificial languages. The model recovers the expected analyses for prototypically agglutinative or fusional languages; for languages which can be analyzed in either way, we demonstrate in the first study that those with variably-realized morphological markers (i.e. ones that are sometimes present, sometimes absent) are less likely to be learned as fusional. In a second study, we show that languages with stress-based vowel reduction are more likely to be learned as fusional. Our model thus provides quantitative support for previous observations that languages with large proportions of agglutinative structures also frequently have large numbers of variably-realized morphs (Plank, 1999) and vowel harmony rather than stress-based reduction (Zingler, 2018).

2 Related work

	Indo-European		Ancient Greek	
	PRS	AOR	PRS	AOR
1SG	*-m-i	*-m	dídō-mi	édō-n
2SG	*-s-i	*-s	dídō-s	édō-s
3SG	*-t-i	*-t	dídō-si	édō

Table 1: Partial set of Indo-European and Ancient Greek (‘give’) person-number forms in present indicative and aorist

We begin with a concrete example of the kind of morphological change we are describing. In some Indo-European (IE) athematic verbs, person and number were expressed cumulatively but tense was realized via a separate morpheme: *-i* for present active indicative and zero for aorist active indicative (Table 1). (These endings are reconstructed for IE but attested in Sanskrit.) However, sound changes between IE and Proto-Greek obscured the unity of the person-number morphs across present and aorist. For example, word-final [m] turned into [n] as a result of sound change, resulting in different 1SG forms in Ancient Greek.⁴ These changes led speakers to reanalyze the formerly separate morphemes as fused (Brian Joseph, p.c.): 1SG.PRS *-mi* vs. 1SG.AOR *-n*. This reanal-

⁴Also, prior to Proto-Greek [t] deleted in some contexts, affecting the 3SG.AOR, and between Proto-Greek and attested Greek [t] → [s] (Brian Joseph, p.c.). Both were regular sound changes but had consequences for morphology.

ysis is evidenced by the fact that in Aeolic dialects, speakers extended the athematic ending *-mi* to verbs that did not historically have it, giving, e.g., *fili-mi* ‘love-1SG.PRS’ where *filō* is expected etymologically. The fact that *-mi* was extended as a single unit indicates that it had undergone fusion.

The reanalysis of the Greek suffixes was thus driven by sound changes that introduced phonological alternations, and in the process introduced ambiguity regarding the morphological structure. In the wake of these changes, speakers were faced with an analytic choice, e.g.: is there one 1SG morpheme *-m* plus a phonological rule, or different 1SG endings *-mi* and *-n* that also express tense?

The extent to which sound change leads agglutinative structures to be reanalyzed as fusional has recently been questioned (Haspelmath, 2018).⁵ Nonetheless, this kind of ambiguity between analyses at different levels of representation is often a driver of language change (Bybee, 1999) and phonological reduction of agglutinative structures is widely cited as a source of fusional (Bybee, 1997; Igartua, 2015, among others). Just as phonological rules and categories can arise when low-level phonetic processes like assimilation are reanalyzed as phonological, so fusion can appear when the effects of phonological process are “baked in” to the morphological representations. Bybee (2002) summarizes the idea (with reference mostly to syntax) with the catchphrase: “Items that are used together fuse together.”

Both Heath (1998) and Zingler (2018) point out the implication that agglutinative constructions must have “barriers”—typological features which prevent them from becoming fusional.⁶ Zingler makes a specific proposal, that fixed (lexical) stress systems tend to encourage fusion, while vowel harmony discourages it. This builds on a typological observation: the kinds of phonological alternations that occur in agglutinative and fusional systems tend to differ, “... with vowel harmony tending to imply agglutination” (Plank, 1999)[310].⁷ Zingler argues that fixed stress leads

⁵In fact, Haspelmath states (pp107-8) that “...we do not know how it is that robust inflectional patterns with cumulative and suppletive affixes arise”. Our paper offers a partial answer.

⁶The argument of Heath (1998) applies to the first (isolating-agglutinative) step of the cycle, rather than the second (agglutinative-fused) as discussed here: he suggests that established agglutinative systems grammaticalize independent function words into morphemes more quickly, due to their analogical similarity to existing morphemes.

⁷An anonymous reviewer questioned the basis for this

to reduction in unstressed syllables, which over time may lose their vowels, placing their consonants in new environments with varied phonological effects. Harmony, on the other hand, prevents the loss of vowels, while at the same time indicating that bound elements are part of the phonological word (since they undergo harmonic changes based on the word stem).⁸

One question here has to do with the relationship between language-level and construction-level properties. From Haspelmath’s perspective, individual constructions may be agglutinative or fusional, but it is not clear that languages as a whole fall into cleanly defined types. However, Zingler’s proposal is rooted in phonology-morphology interactions. Phonological processes generally operate across a range of constructions in a language. Phonological properties are language-level and thus might be expected to have an across-the-board effect on morphological structure. Moreover, accumulation of effects on individual constructions may result in a disproportionate number of constructions of the same type (agglutinate, fusional, etc.) in a given language. In other words, there is no expectation that the ways constructions develop historically will be fully independent of each other. To the extent that the phonological context is the same for different morphological constructions, we might expect similar pressures in and outcomes of language change. While Zingler himself does not say so, his ideas stand as an implicit challenge to Haspelmath’s questioning of the validity of morphological types at the language level.

We argue below that the presence of variably-realized morphological marking is also a protective factor against fusion. Many agglutinative languages have position classes that are sometimes filled by an overt morph, and sometimes not; this is what we mean by ‘variably-realized’ morphological marking. Examples include morphosemantic markers such as causatives, desider-

generalization, pointing out that both Algonquian and Nilotic languages have vowel harmony, but the former would be classified as agglutinative and the latter as fusional. While we agree with the reviewer that more typological investigation is warranted, we follow Plank and others in the claim that there is a typological correlation to be explained.

⁸Plank (1998)[201] points out that this idea of vowel harmony ‘cementing’ the internal cohesion of agglutinative word structure goes back to Baudouin de Courtenay (1876), but is not unproblematic in its reasoning. In our work, nothing depends on vowel harmony creating greater word-internal cohesion.

1	Input MSPs	$M_1=I, M_3=I, STEM=1$
	Transducer 1: fusion	
2	Abstract ms	$M_1=I M_3=I, STEM=1$
	Transducer 2: lexicon	
3	Underlying	mwi-mela
	Transducer 3: phonology	
4	Surface form	mwimela

Figure 1: Overall architecture of our model, consisting of three finite-state transducers, producing two intermediate layers of latent representation (in gray).

atives or negatives, whose position class slots are filled only when that meaning occurs, and optional agreement marking (Plank, 1999). Polysynthetic languages, which are invariably mostly agglutinative, contain even more variably-realized elements, such as incorporated objects (Comrie, 1989). We suggest that, because variably-realized elements break up sequences of morphemes that would otherwise always appear next to one another, they render fusional analyses less appealing to the learner. Our argument not only explains the previous observation that variably-realized marking and agglutination correlate, but might also help to explain where and how fusional development.

Caballero and Kapatsinski (to appear) quantify fusional in the Uto-Aztecan polysynthetic language Choguita Rarámuri. They show that morphemes exhibit some fusion, especially close to the stem. Their research focus is similar to ours in examining how learners might infer morphological boundaries. However, their approach differs from our own in two ways. First, it provides a description of how much fusion is present based on the Naive Discriminative Learner (Baayen et al., 2011) and some variant models, but not a causal model of how language properties encourage or discourage fusion. Second, it lacks an explicit model of phonological rules. Caballero and Kapatsinski point out that if learners can mentally “undo” the effects of regular phonological rules, the Naive Learner will overestimate the degree of fusional. The model we present below is designed to test causal mechanisms underlying the development of fusional, and specifically the role of phonological rules.




Figure 2: Fragment of first transducer, from MSPs to abstract morphemes. (For compactness, only one MSP per morphosyntactic category is shown.)

3 Model

Our model is intended to capture the first stage of the transition from agglutination to fusion, in which the learner reanalyzes an ambiguous polymorphemic structure as monomorphemic. This reanalysis is covert, affecting only the learner’s mental representation; in order for the surface system to become unambiguously fusional (i.e. for the change to become actualized, in the terminology of historical linguistics), the reanalyzed marker must generalize to other words, as we saw above for Greek, or undergo further diachronic changes. We leave modeling such changes for future work.

The model (Figure 1) formalizes our intuitions about agglutinative and fusional analyses of morphological systems. In order to do so, it represents morphemes as invariant underlying representations and applies phonological processes that transform them into surface forms. Because the popular sequence-to-sequence framework for inflection (Kann and Schütze, 2016) conflates these processes within a single neural network, we choose instead to extend an older model, Cotterell et al. (2015), in which these components are separate. While this model may be less capable overall, it is more interpretable in terms of the theoretical questions we are trying to answer.

Cotterell et al. model the correspondence between sequences of abstract morphemes and surface strings. The term “abstract morpheme” refers to a set of MSPs that already reflect the effects of fusion— in the context of agglutination, each abstract morpheme is a single MSP, whereas for fusion, the abstract morphemes bundle together many MSPs. The model maps abstract morphemes to surface strings in the following steps: first, each abstract morpheme is assigned an underlying phonological form; next, these forms are concatenated to yield an underlying inflected form; finally, this form is passed through a finite-state transducer which applies (stochastic) phonological rules. (Lines 2-4 of Figure 1.)

Our model differs from theirs primarily in

adding a new initial step, which maps a sequence of atomic MSPs into a corresponding sequence of abstract morphemes. This is the step at which fusion occurs. For instance, a sequence $STEM=give, NUM=PL, TENSE=PRS$ could be output as three separate symbols, or as $STEM=give, NUM=PL|TENSE=PRS$, where we use the $|$ notation to indicate that two MSPs are fused into a single abstract morpheme. The model simplifies slightly by requiring uniformity at the level of morphosyntactic categories; in our illustrating example, either all combinations of number and tense MSPs would be fused or none would be.⁹

For simplicity, we also modify the model so that it consists of a cascade of relatively small finite-state transducers (FSTs) (Mohri et al., 2002) which we can implement using the Carmel package (Graehl, 1997). This necessitates some changes and simplifications to the model, but allows us to use Carmel’s built-in Bayesian inference (Chiang et al., 2010) rather than belief propagation as in Cotterell et al. (2015).

As stated, the first transducer in the cascade maps a sequence of MSPs into a sequence of abstract morphemes (without specifying any phonological detail). For computational convenience, we make two simplifying assumptions: The input MSPs are provided in a fixed, templatic order (Stump, 1997), in which only contiguous subsequences can be fused. MSPs are not allowed to fuse with the stem (that is, there is no MSP-conditioned stem allomorphy), even though this occurs in real languages. The transducer (Fig 2) first chooses an allowable fusion template via epsilon transition and then deterministically transforms the input sequence.

The second transducer is a lexicon (Figure 3) which maps each abstract morpheme to a phonological underlying form. Cotterell et al. implement this as a distribution of point masses on strings, which is intractable and must be approximated.¹⁰ We use a simpler solution which is finite-

⁹In real languages, individual MSPs (or even individual allomorphs of MSPs) can fuse, even when other MSPs belonging to the same categories do not. Stump (2001)[139–144] gives examples under the heading of ‘portmanteau rule blocks’. In Swahili verbs, subject agreement prefixes and the negative prefix *ha-* normally have separate realizations and occupy adjacent position classes. However, the combination of 1SG.SBJ (normally *ni-*) and NEG is realized as a single, fused prefix *si-*.

¹⁰It has the advantages that strings are not limited in length, and that the morpheme may vary over two unrelated phono-




Figure 3: Fragment of second transducer, from abstract morphemes to characters. Only the lexical entry for $M_1=1$, only three steps in the linear chain, and only the character h are shown.




Figure 4: Fragment of third transducer responsible for altering i to y . X stands for any character, V for any vowel and C for any consonant.

state and tractable. Each word in the lexicon has an initial state with two outgoing epsilon transitions; one leading back to the start state (thus producing a null morpheme) and another leading to a linear chain of 15 states. Each state in the chain can produce any non-null character, or transition back to the start. This transducer can produce any string up to 15 characters long; the posterior tends to concentrate around a single underlying form per morpheme. We set the prior odds ratio for the two initial transitions so that the null morpheme is 100 times more likely *a priori* than the linear chain. This prior biases the model toward parsimonious analyses with smaller morpheme inventories, provided they can satisfactorily account for the data.

The third transducer (Figure 4) implements phonological rules. While Cotterell et al. supply a full finite-state phonology (Riggle, 2004; Hayes and Wilson, 2008, and others), in our experiments below, we use a custom machine implementing only the specific rules which actually exist in our artificial language. However, the machine executes the rules non-deterministically; the system must learn the true probability with which the rules occur. Again, we use prior parameters to determine how much evidence is necessary to convince the system that a phonological rule is justified. In our experiments below, we set the prior odds ratio of the rule applying to 1:100. In simulation \mathcal{C} , we vary the strength of the prior (by multiplying the prior counts by a constant α) and report logical forms without reserving mass for “hybrid” versions.

Underlying	Surface	Gloss
ndi-i-ko:mala	ndi:ko:mala	‘I am sitting’
u-i-ko:mala	wi:ko:mala	‘You.SG are sitting’
a-i-ko:mala	i:ko:mala	‘S/he is sitting’
tu-i-ko:mala	twi:ko:mala	‘We are sitting’
mu-i-ko:mala	mwi:ko:mala	‘You.PL are sitting’
va-i-ko:mala	vi:ko:mala	‘They are sitting’

Table 2: Conjugation of a Kihehe verb in the present tense (Johnson, 2015).

results as a function of this parameter.

We perform posterior inference using blocked Gibbs sampling (Chiang et al., 2010). For each language, we run 20 Markov chains with random starting points, annealing linearly from temperature 4 to 1 over 200 iterations. We average the final counts from each chain to obtain the posterior.

4 Case study 1: Variably-realized marking

In this section, we run a series of simulations on artificial languages, intended to be reminiscent of the Bantu language Kihehe, spoken in Tanzania (Lewis, 2009). Simulations $\mathcal{A} - \mathcal{B}$ show that the model can learn both agglutinative and fusional systems; \mathcal{C} shows that the model’s preference for fusional systems is dependent on the phonological prior weight α . \mathcal{D} gives the main conclusion, that the presence of a variably-realized marker between two obligatory ones can block the emergence of fusion.

We first give a brief overview of Kihehe itself. Kihehe verbs are marked for person-number agreement with the subject; the form of the agreement marker reflects the noun class of the subject. This marker is sometimes followed by a tense marker. Although Kihehe has morphemes which begin with vowels, its phonological rules act to prevent onsetless syllables from surfacing, by transforming the first vowel in a VV sequence into a glide, or deleting one vowel, and in both cases, lengthening the remaining vowel (Odden and Odden, 1999).¹¹ This creates a system in which agreement and tense markers are arguably fused on the surface (Table 2). In 3SG and 3PL, where vowel deletion occurs, segmentation is impossible. In the other cells, segmentation of the surface form is possible but gliding prevents postulation of a single, invariant form of each agree-

¹¹We present these phonological processes here as SPE rules, although of course other theoretical frameworks like OT could derive the same results.

Name	M_1	M_2	M_3	Phonology	Examples
\mathcal{A}	$\begin{cases} ta \\ ko \\ he \\ mu \\ gu \\ si \end{cases}$	-	$\begin{cases} i \\ a \\ de \\ no \end{cases}$		koimela, muimela
\mathcal{B}	$\begin{cases} ya, se, dunu, lanu \\ ha, hi, si, yu \\ yi, wa, bise, logi \\ \dots \end{cases}$				dunumela, yamela
\mathcal{C}	as \mathcal{A}	-	as \mathcal{A}	$\begin{bmatrix} V \\ +high \end{bmatrix} \rightarrow \text{glide} / _V$ $V \rightarrow \phi / _V$	mwimela (< mu-i-mela), kamela (< ko-a-mela)
\mathcal{D}	as \mathcal{A}	$\begin{cases} sa \\ \epsilon \end{cases}$	as \mathcal{A}	as \mathcal{C}	mwimela (< mu-i-mela), musimela (< mu-sa-i-mela)

Table 3: Morphophonology of four simulated languages (case study 1).




Figure 5: Probability of fusion in \mathcal{A} vs \mathcal{B} .

ment marker. This parallels the conditions in pre-Greek that led to reanalysis of separate person-number and tense morphemes as fused (Table 1 above).

As in Kihehe, our artificial languages have stems made up of CV syllables. We use an inventory of 5 vowels and 15 consonants; for each language, we generate 200 unique random stems, with length $\min(5, \text{Geom}(.5))$, which we use to create a corpus of 1000 inflected forms. Each language has two required morphosyntactic categories, M_1 and M_3 (e.g., person and tense), realized as prefixes, with uniformly distributed values (MSPs). In simulation \mathcal{D} , we explore the impact of a variably-realized category M_2 which appears between the two. Table 3 shows the realizations of M_1 , M_2 and M_3 and the phonology in each simulation.

Language \mathcal{A} is prototypically agglutinative. Each category:property (MSP) pair licenses a unique, segmentable morph in the surface string. (The morphs that realize M_1 contain equal numbers of high and low vowels, and for M_3 contain equal numbers of vocalic and consonantal

onsets.) Language \mathcal{B} is prototypically fusional. While words inflect for the same categories as in language \mathcal{A} , each M_1, M_2 value pair licenses a unique morph that realizes both categories (a sampled string of one or two syllables). We expect the model to analyze \mathcal{A} as agglutinative, due to the prior preference for a small morpheme inventory (the agglutinative analysis has $6+4=10$ morphemes while the fusional analysis has $6*4=24$), and \mathcal{B} as fusional; this is the actual result (Figure 5).

Language \mathcal{C} has the same underlying properties as language \mathcal{A} , but is subject to phonological rules which result in non-isomorphic relationships between form and meaning in the surface forms. (The surface prefixes are thus segmentable, but not into invariant forms; for example, *ko-* alternates with *k-* and *mu-* with *mw-*, conditioned on their phonological environment.) We use language \mathcal{C} to explore the effects of the prior parameter α , which encodes our bias against using the phonological rule; larger α means that more evidence is required to justify the rule’s existence. Not surprisingly, small α leads to agglutinative analyses, while large α leads to fusion (Figure 6, top).

Finally, we investigate the effects of M_2 , a variably-realized category between M_1 and M_3 , using language \mathcal{D} . For this simulation, we set $\alpha = 1000$, a setting which we found in the previous experiment would result in a fusional analysis. We do so because we are interested in whether M_2 can *prevent* fusion from occurring; thus, it makes sense to start from a setting in which fusion is expected. All versions of language \mathcal{D} have the category M_2 between M_1 and M_3 , but we vary the




Figure 6: Fusion in (top) \mathcal{C} as a function of α , (bottom) \mathcal{D} as a function of the probability of non-zero M_2 .

probability with which it takes its non-zero value (realized as *sa-*). We find (Figure 6, bottom) that when *sa-* always or never occurs, the posterior mode is a fully fused system, $M_1|M_2|M_3$. But when *sa-* is variably realized, full fusion essentially never occurs. Instead, we find either agglutination ($M_1-M_2-M_3$, the plurality outcome when $p(sa) = .25$) or partial fusion, in which M_2 is realized jointly with one of its neighbors.

Thus, the important result is that in the context of phonological rules that create surface-ambiguous word-forms, variably-realized morphemes decrease the likelihood of agglutinative morphemes being reanalyzed as fusional.

5 Case study 2: Stress-based vowel reduction

Our next study addresses Zingler’s claims about Turkish agglutination. Zingler argues (p422) that languages have various mechanisms for articulatory reduction of vowels. One of these is vowel harmony, which replaces some distinctive features of a vowel with those of its neighbor, and another is durational reduction, which reduces a vowel’s absolute length, and tends to erode its features by centralizing it. These mechanisms are complementary; harmony correlates with syllable-timed languages and with systems that assign stress to a fixed syllable relative to the word boundary. Durational reduction correlates with stress-timed languages and with systems in which the stressed syllable is lexically determined. Zingler’s hypothe-




Figure 7: The transducer for vowel reduction (with final stress).

sis is that durational reduction leads to fusion, and that vowel harmony, as an alternative way to ease articulation without durational reduction, is what prevents Turkish from becoming fusional.¹²

In this section, we validate Zingler’s claim that vowel reduction tends to encourage the development of fusion, and add to his idea by showing that this is especially so when the position of reduction is predictable within particular morphemes. Simulation \mathcal{E} investigates the case where stress is predictable within morphemes, and \mathcal{F} the case where it is not. As above, we use artificial languages in which stems consist of CV syllables. Languages in this section have two required categories, M_1 and M_2 , realized as suffixes. Table 4 shows the realizations of M_1 and M_2 and the phonology.

We next apply vowel reduction. In simulation \mathcal{E} we apply final stress and then alternate strong and weak syllables moving left; the reduction rule deletes each weak vowel with some probability.¹³ So, the word *dite-ko-de* in fully reduced form would become *dtekde*. Simulation \mathcal{F} is similar, but with initial stress, so *dite-ko-de* would become *ditekod*. Such stress rules follow from the core predictions of metrical stress theory (Hayes, 1995).¹⁴ Within each simulation, we compare languages with varying rates of reduction, ranging from no reduction to all unstressed vowels reduced.

Although neither \mathcal{E} nor \mathcal{F} has a true lexical stress system, the varying stress rules have implications for the predictability of stress placement

¹²Zingler also argues that vowel harmony helps maintain a morpheme minimality criterion. He does not consider whether morpheme minimality plays a role in preventing fusion, but we believe this could also be relevant and could be simulated in our model, with suitable alterations to the lexicon. But we leave doing so for future work.

¹³This approximates the ‘fall of the jers’, a sound change in the history of the Slavic languages (Kiparsky, 1979).

¹⁴Kager (1995) gives example languages which have the stress systems described here. Weri parses feet from right-to-left, with final stress; Hungarian parses from left to right with initial stress.

Name	M_1	M_2	Phonology	Examples
\mathcal{E}	$\begin{cases} ta \\ ko \\ he \\ mu \\ gu \\ si \end{cases}$	$\begin{cases} pi \\ ka \\ de \\ no \end{cases}$	Assign sS stress from right $[\text{ C voice-}x] \rightarrow [\text{ voice-}y] / _ [\text{ C voice-}y]$	ddekete (< dite-ko-de)
\mathcal{F}	As \mathcal{E}	As \mathcal{E}	Assign Ss stress from left $[\text{ C voice-}x] \rightarrow [\text{ voice-}y] / _ [\text{ C voice-}y]$	ditkod (< dite-ko-de)

Table 4: Morphophonology of two simulated languages (case study 2).

on morphemes. Because each word has two obligatory suffixes, final stress (simulation \mathcal{E}) means that the second suffix, corresponding to M_2 , will always be pronounced with a full vowel, while the suffix for M_1 will be probabilistically reduced. The same condition would hold in a true lexical stress language, although in such a language it would *also* hold if the number of suffixes were variable. In \mathcal{F} , however, stress lands on the suffix realizing M_1 when the length of the stem is even, on the suffix for M_2 when it is odd. Thus, each suffix appears in both strong and weak positions.

Vowel reduction disrupts the original CV structure of our languages, allowing consonant clusters to appear on the surface. It is extremely common for such clusters to simplify for articulatory reasons (Brohan and Mielke, 2018)— we apply only one simplification rule, progressive voicing assimilation. Thus, *dtekte* would surface as *ddekete*. In a real language, we might expect further simplifications to apply to prevent, for instance, geminate *dd* at the beginning of a word; for our purposes, however, a single assimilation rule is sufficient.

We apply the same learning procedure as in the previous section. The feature and lexicon transducers are unchanged. The transducer for vowel reduction is shown as Figure 7; the transducer for assimilation resembles the one in Figure 4. We use $\alpha = 1000$ as a bias parameter to penalize both phonological rules (vowel reduction and consonant assimilation).

Figure 8 (top) shows the results for language \mathcal{E} . With reduction rate 0 (no reduction), the posterior mode is an agglutinative system. Optional vowel reduction (25-75%) produces mixed systems in which both agglutination and fusion are recognized as possible analyses, although the posterior probability of fusional analyses climbs slightly as reduction increases. With 100% reduction, the posterior strongly prefers fusion.

The orange line shows the posterior probability




Figure 8: Probability of fusion and vowel reduction in (top) \mathcal{E} , (bottom) \mathcal{F} as a function of the probability of vowel reduction.

of vowel reduction. The system always underestimates the true probability of reduction— when the true probability is 50%, for instance, the posterior is only 20%— and counterintuitively, learns that reduction is *absent* when its true probability is 100%. This reflects the influence of the prior bias against the reduction rule, but also the fact that the system learns some cases of reduction as variant lexical items. Table 5 shows one Markov chain’s final learned representations for two values of M_1 (*-ta*) and M_2 (*-de*) as a function of reduction rate. With no reduction, the system learns only agglutinative analyses; intermediate systems learn underlying forms for both fused and unfused morphemes, including multiple variant forms of each one. The system with 100% reduction learns only a fused morpheme, *-tte*, which incorporates the result of both vowel reduction and assimilation. With no evidence for an overt vowel between the *ts*, the system has no reason to learn the rule.

Figure 8 (bottom) shows the results for lan-

Rate	$M_1=I$	$M_2=III$	$M_1=I M_2=III$
0	ta	de	-
25	ta (t, te)	de (te)	tade
50	ta (t)	te (de)	tade
75	ta (ti, t)	te (de)	tte
100	-	-	tte

Table 5: Underlying forms learned for two morphemes in variants of language \mathcal{E} . First entry is the posterior mode, (parentheses) show alternatives with $p > .01$.

guage \mathcal{F} . As predicted, the probability of fusion increases again with the rate of reduction, but the results are less extreme, since stress placement on the suffixes varies depending on the stem. For this language, agglutination is always the plurality outcome, but intense reduction increases the probability that some fusional analyses will be produced.

Returning to Zingler’s argument, Turkish is similar to the case in which the probability of reduction is 0, a case which in our simulations is indeed strongly agglutinative. Because Turkish is syllable-timed and has vowel harmony, it is unlikely to develop the alternate pattern of stress-timing and durational reduction which Zingler argues could lead it to develop more fusion. We have shown that stress-timing and durational reduction does favor fusional analyses. It is tempting to speculate that the same argument might help to explain the differences between Finnish (vowel harmony and agglutination) and Estonian (no harmony and limited fusion); Estonian historically had a more agglutinative structure. In particular, we note that Estonian has word-initial stress (Lipus et al., 2014), which simulation \mathcal{F} shows is predictive of a mixed rather than entirely fusional system.

6 Conclusion

Our results show that, at least in principle, pre-existing typological features can help to determine whether an agglutinative construction evolves into a fusional one, or remains stable. In particular, we present firm evidence that variably-realized marking makes fusion less likely while durational vowel reduction has the opposite effect. While authors like Plank (1999) have listed many independent features or elements which characterize prototypically “fusional” morphology, these have typically been discussed as typological clusters, without necessarily providing a causal explanation. Our modeling results give a mechanism in which some of these features precede, and give

rise to, others.

A variety of researchers have noted (Greenberg, 1966) and attempted to discover (Murawaki, 2018; Bjerva et al., 2019) correlations between typological features. Harris (2008) suggests that in many cases, such correlations reflect precisely this kind of historical mechanism—the likelihood that a language will develop in some typological direction is dependent on the features it already has, some of which may encourage a particular change while others tend to reinforce existing patterns. While the simulations presented here use artificial data, we hope to apply this model to real corpus data from languages in which fusion might be developing, in order to isolate particular changes in the phonology as the “triggers” of ongoing morphological change, or explain distributionally why one set of morphemes appears more fusional than another. In doing so, we can discover how theoretical explanations of language change, such as the morphological cycle, might be realized in the minds of language users.

Acknowledgments

We thank the members of the Fall 2018 Seminar on Models of Morphological Learning and Change at OSU for their comments on preliminary versions of this project, Brian Joseph for discussion of historical examples, as well as three anonymous reviewers.

References

- R Harald Baayen, Petar Milin, Dušica Filipović Djurdjević, Peter Hendrix, and Marco Marelli. 2011. An amorphous model for morphological processing in visual comprehension based on naive discriminative learning. *Psychological review*, 118(3):438–481.
- Johannes Bjerva, Yova Kementchedjhieva, Ryan Cotterell, and Isabelle Augenstein. 2019. [A probabilistic generative model of linguistic typology](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 1529–1540. Association for Computational Linguistics.
- Anthony Brohan and Jeff Mielke. 2018. Frequent segmental alternations in P-base 3. In Larry Hyman and Frans Plank, editors, *Phonological typology*, pages 196–228. de Gruyter.
- Joan Bybee. 1997. Semantic aspects of morphological typology. In Joan Bybee, John Haiman, and Sandra A. Thompson, editors, *Essays on language*

- function and language type: Dedicated to T. Givón*, pages 25–37. John Benjamins.
- Joan Bybee. 1999. Usage-based phonology. In Michael Darnell, Edith A. Moravcsik, Michael Noonan, Frederick J. Newmeyer, and Kathleen Wheatley, editors, *Functionalism and formalism in linguistics, vol. 1: General papers*, pages 211–242. John Benjamins.
- Joan Bybee. 2002. *Frequency of use and the organization of language*. Oxford University Press.
- Gabriela Caballero and Vsevolod Kapatsinski. to appear. How agglutinative? searching for cues to meaning in Choguita Rarámuri (Tarahumara) using discriminative learning. In Andrea D. Sims, Adam Ussishkin, Jeff Parker, and Samantha Wray, editors, *Morphological typology and linguistic cognition*. Cambridge University Press.
- David Chiang, Jonathan Graehl, Kevin Knight, Adam Pauls, and Sujith Ravi. 2010. Bayesian inference for finite-state transducers. In *Human Language Technologies: The 2010 Annual Conference of the North American Chapter of the Association for Computational Linguistics*, pages 447–455. Association for Computational Linguistics.
- Bernard Comrie. 1989. *Language universals and linguistic typology: Syntax and morphology*. University of Chicago Press.
- Ryan Cotterell, Nanyun Peng, and Jason Eisner. 2015. Modeling word forms using latent underlying morphs and phonology. *Transactions of the Association for Computational Linguistics*, 3:433–447.
- Jan Baudouin de Courtenay. 1876. Rez’ja i rez’jane. *Slavjanskij sbornik*, 3:223–371.
- Jonathan Graehl. 1997. [Carmel finite-state toolkit](#). *ISI/USC*.
- Joseph H. Greenberg. 1966. *Language universals: With special reference to feature hierarchies*. Walter de Gruyter.
- Riho Grünthal. 2007. Morphological change and the influence of language contacts in Estonian. In Hans Fix, editor, *Beiträge zur Morphologie. Germanisch, baltisch, ostseefinnisch, Odense*, pages 403–432. John Benjamins.
- Alice C. Harris. 2008. On the explanation of typologically unusual structures. In Jeff Good, editor, *Linguistic universals and language change*, pages 54–76. Oxford University Press.
- Martin Haspelmath. 2009. An empirical test of the agglutination hypothesis. In Sergio Scalise, Elisabetta Magni, and Antonietta Bisetto, editors, *Universals of language today*, pages 13–29. Springer.
- Martin Haspelmath. 2018. Revisiting the anasyntetic spiral. In Bernd Heine and Heiko Narrog, editors, *Grammaticalization from a typological perspective*, pages 97–115. Oxford University Press.
- Bruce Hayes. 1995. *Metrical stress theory: Principles and case studies*. University of Chicago Press.
- Bruce Hayes and Colin Wilson. 2008. A maximum entropy model of phonotactics and phonotactic learning. *Linguistic Inquiry*, 39(3):379–440.
- Jeffrey Heath. 1998. Hermit crabs: Formal renewal of morphology by phonologically mediated affix substitution. *Language*, 74(4):728–759.
- Hans Henrich Hock and Brian D. Joseph. 1996. *Language history, language change and language relationship: An introduction to historical and comparative linguistics*. Mouton de Gruyter.
- Iván Igartua. 2015. From cumulative to separative exponence in inflection: Reversing the morphological cycle. *Language*, 91(3):676–722.
- Martha Booker Johnson. 2015. The beginnings of a sketch grammar on Kihehe. Technical report, Ohio State University.
- René Kager. 1995. The metrical theory of word stress. In John A. Goldsmith, editor, *The handbook of phonological theory*, pages 367–402. Blackwell.
- Katharina Kann and Hinrich Schütze. 2016. MED: The LMU system for the SIGMORPHON 2016 shared task on morphological reinflection. In *Proceedings of the 14th SIGMORPHON Workshop on Computational Research in Phonetics, Phonology, and Morphology*, pages 62–70.
- Shuan Karim. 2019. Competition between formatives and the diversity of ezafat. In *Proceedings of the 24th International Conference on Historical Linguistics (ICHL24)*.
- Valentin Kiparsky. 1979. *Russian historical grammar*. Ardis.
- M. Paul Lewis, editor. 2009. *Ethnologue: Languages of the World*, sixteenth edition. SIL International, Dallas, TX, USA.
- Pärtel Lippus, Eva Liina Asu, and Mari-Liis Kalvik. 2014. An acoustic study of Estonian word stress. *Proc. Speech Prosody 2014*, pages 232–235.
- Mehryar Mohri, Fernando Pereira, and Michael Riley. 2002. Weighted finite-state transducers in speech recognition. *Computer Speech & Language*, 16(1):69–88.
- Yugo Murawaki. 2018. [Analyzing correlated evolution of multiple features using latent representations](#). In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 4371–4382. Association for Computational Linguistics.

- David Odden and Mary Odden. 1999. Kihehe syllable structure. In Harry van der Hulst and Nancy A. Ritter, editors, *The syllable: views and facts*, pages 417–446. Walter de Gruyter.
- Frans Plank. 1998. The co-variation of phonology with morphology and syntax: A hopeful history. *Linguistic Typology*, 2:195–230.
- Frans Plank. 1999. Split morphology: How agglutination and flexion mix. *Linguistic Typology*, 3:279–340.
- Jason Alan Riggle. 2004. *Generation, recognition, and learning in finite state Optimality Theory*. Ph.D. thesis, University of California, Los Angeles.
- Gregory T. Stump. 1997. Template morphology and inflectional morphology. In Geert Booij and Jaap van Marle, editors, *Yearbook of morphology 1996*, pages 217–241. Kluwer.
- Gregory T. Stump. 2001. *Inflectional morphology: A theory of paradigm structure*. Cambridge University Press.
- Tim Zingler. 2018. Reduction without fusion: Grammaticalization and wordhood in Turkish. *Folia Linguistica*, 52(2):415–447.